



# 3MP IR Mini Bullet Camera



## Key features

- 3 megapixel (2048 x 1536) high resolution
- Full HD1080p real-time video
- 3D DNR & DWDR & BLC
- IR LEDs: up to 30m
- IP66
- PoE
- Compact design

## Dimensions



HDS-2032IRP	
<b>Camera</b>	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.07 lux @F1.2, AGC ON 0 lux with IR
Shutter time	1/25s (1/30s) ~ 1/100,000s
Lens	4mm @F2.0, angle of view: 75.8° (6mm, 12mm optional)
Lens mount	M12
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
<b>Compression Standard</b>	
Video compression	H.264 / MJPEG
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
<b>Image</b>	
Max. Image Resolution	2048 x 1536
Frame rate	50Hz: 12.5fps (2048 x 1536), 25fps (1920 x 1080), 25fps (1280 x 720) 60Hz: 15fps (2048 x 1536), 30fps (1920 x 1080), 30fps (1280 x 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
<b>Network</b>	
Network storage	NAS (iSCSI optional)
Alarm trigger	motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos, IPv6 (SIP, SRTSP optional)
Interoperability	ONVIF, PSIA, CGI
Security	User Authentication, reset button, dual stream, watermark
<b>Interface</b>	
Communication interface	1 RJ45 10 M / 100 M Ethernet port
<b>General</b>	
Operating conditions	-30 °C ~ 60 °C (-22°F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	Max. 5W (7W with ICR on)
Weather proof rating	IP66
IR range	Up to 30m
Dimension	60.4 x 76.9 x 139.2mm
Weight	500g (1.1lbs)

\* Product picture and technical specs subject to change without previous notice.  
For further information, please contact our local sales team.