

## HDS-AT7264IR-A series

### High definition IR PTZ Dome Camera



### Key feature

#### IR function:

- 0 Lux minimum illumination
- Up to 120m IR distance
- IR light MTBF reaching up to 30,000 hours

#### System function:

- 1/4" high performance Sony CCD
- $\pm 0.1^\circ$  Preset Accuracy
- Self-adaptive to Pelco-P/D protocol
- 3D intelligent positioning function
- Power-off memory function: restore PTZ & Lens status after reboot
- Built-in temperature sensor, display internal temperature
- IP66 standard (outdoor dome)
- Scheduled PTZ movement

#### Camera function:

- Auto focus, auto white balance, and auto/manual day & night switch
- Privacy masks programmable
- Support 3D DNR, DWDR and digital zoom

#### PTZ function:

- 360° endless pan range and -15°-90° tilt range
- 240°/s Pan Preset Speed and 200°/s Tilt Preset Speed
- 0.1°-160°/s Manual Pan Speed and 0.1°-120°/s Manual Tilt Speed
- 256 presets programmable; preset image freezing capability
- 8 patrols, up to 32 presets per patrol
- 4 patterns, with the total recording time not less than 10 minutes

- Proportional zoom function
- Park action: auto call up of PTZ movement, after a defined time of inactivity

## Application Scenarios


It can be widely applied to places with no lights or weak lights requiring wide-area and high-speed monitoring, such as rivers, forests, highways, railways, airports, ports, sentries, squares, parks, scenic sites, streets, stations, large venues, outside of residential areas, etc.

## Specifications

Model Parameter		HDS-AT7264IR-A
		High definition IR PTZ Dome Camera
Camera	Image Sensor	1/3" Sony Interline Transfer Exview HAD- II CCD
	Effective Pixel	PAL: 976(H)×582(V)
	Horizontal Resolution	Color: 700 TVL B/W: 750 TVL
	Signal System	PAL/NTSC
	Min. Illumination	Color: 0.02Lux/(F1.6, AGC ON),0.0008Lux/(F1.6, AGC ON, IRE×256) B/W: 0.002Lux/(F1.6, AGC ON),0.00008Lux/(F1.6, AGC ON, IRE×256) 0 Lux with IR
	White Balance	Auto / One touch WB/ ATW / Indoor / Outdoor
	AGC	Auto / Manual
	S / N Ratio	≥ 50dB
	DNR	High/Medium/Low/off
	WDR	128x(On/Off/Auto)
	Shutter Time	PAL: 1-1/10,000s NTSC: 1-1/10,000s
	Day & Night	IR Cut Filter
	Digital Zoom	16x
	Privacy Mask	8 privacy masks programmable; a maximum of 8 zones can be masked simultaneously on the same video screen
Focus Model	Auto / Semiautomatic / Manual	
Lens	Focal Length	4-92mm, 23X
	Zoom Speed	Approx.4.0s(Optical Wide-Tele)
	Angle of View	57.58-3.12 degree(Wide-Tele)
	Min. Working Distance	10-1500mm (Wide-Tele)
	Aperture Range	F1.6-F3.7
Pan and Tilt	Pan Range	360° endless
	Pan Speed	Pan Manual Speed: 0.1°-160°/s, Pan Preset Speed: 160°/s
	Tilt Range	-2°-90° (Auto Flip )
	Tilt Speed	Tilt Manual Speed: 0.1°-120°/s, Tilt Preset Speed: 120°/s

	Proportional Zoom	Rotation speed can be adjusted automatically according to zoom multiples
	Number of Preset	256
	Patrol	8 patrols, up to 32 presets per patrol
	Pattern	4 patterns, with the total recording time not less than 10 minutes
	Power-off Memory	Support
	Park Action	Preset / Patrol / Pattern / Pan scan / Tilt scan / Random scan / Frame scan / Panorama scan
	PTZ Position Display	On / Off
	Preset Freezing	Support
	Password Protection	Support
	Zone Scanning/Display	Scanning within programmed zone, display zone title
	Camera Title	Programmable title display
	Compass	Support , the north can be set
	Scheduled Task	Preset / Patrol / Pattern / Pan scan / Tilt scan / Random scan / Frame scan / Panorama scan
	RS-485 communication diagnosis	Support
	Manchester code and connection failures diagnosis	Support
<b>Infrared</b>	IR Range	120m
	IR irradiation angle	Automatically adjusted, depending on the zoom ratio
<b>Input/ Output</b>	Monitor Output	1.0V[p-p] / 75Ω, PAL or NTSC composite, BNC
<b>General</b>	Menu Language	English/Chinese
	RS-485 Protocols	Pelco-P, Pelco-D, self-adaptive
	Power	24 VAC Max.50W(IR LED On, Heater On) Max.24W(IR LED On) Max.15W(IR LED Off, Heater Off)
	Working Temperature / Humidity	-30 ℃-65℃(-22℉-149℉)(outdoor dome) 90% or less
	Protection Level	IP66 standard (outdoor dome) TVS 4,000V lightning protection, surge protection and voltage transient protection
	Mounting	Various mounting modes optional
	Dimensions	Φ245 ×399mm (Φ9.65" ×15.71" ) (Outdoor)
	Weight (approx.)	5.5kg(12.13lbs)
	Mount Option (only suitable for outdoor dome)	Long-arm wall mount; Pendent mount; Ceiling mount

## Dimensions



## Accessories



Long-arm wall mount bracket